

# Mechanics Truck DOMINATOR® CS

## Technical Specifications

Commercial Vehicles



Specification	11 ft
Body Rating	10,000 ft-lb (1.46 tm)
Body Weight	2200 – 2300 lb (998 – 1043.3 kg)
Body Width (including rain eaves)	96" (243.8 cm)
Sidepack Height	52" (132.1 cm) with optional RH 60"H (152.4 cm)
Sidepack Depth	22" (55.9 cm)
Cargo Deck Width	50" (127 cm)
Step Bumper Depth (if without loadgate)	21" (53.3 cm)
Tailgate Height (if without loadgate)	10" (25.4 cm)
Storage Capacity (including workbench)	120.5 – 142.2 cu ft (3.4 – 4.0 m <sup>3</sup> ) (based of configuration)
Angle of Departure	17° (0.29 rad) with crank-down outrigger 14° (0.24 rad) with crank-down outrigger
<b>Door Opening Dimensions – 52"H Sidepacks:</b>	
LH 1st Vertical	29.5"W x 46.5"H (74.9 cm x 118.1 cm)
LH 2nd Vertical	16.5"W x 46.5"H (41.2 cm x 118.1 cm)
LH Horizontal	44.5"W x 29"H (113 cm x 73.7 cm)
LH Rear	18"W x 46.5"H (45.7 cm x 118.1 cm)
RH Front Vertical (52"H [132.1 cm] option)	49"W x 46.5"H (124.5 cm x 118.1 cm)
RH Front Vertical (60"H [152.4 cm] option)	49"W x 54.5"H (124.5 cm x 138.4 cm)
RH Horizontal	44.5"W x 29"H (113 cm x 73.7 cm)
RH Rear	18"W x 46.5"H (45.7 cm x 118.1 cm)



An Oshkosh Corporation Company



## Standard Configuration

11 ft RH and LH standard sidepacks 52" (132.1 cm)  
11 ft RH front raised\* 60" (152.4 cm)

\*Includes 1st and 2nd vertical.

## Body Materials

The sidepacks are constructed of 14-gauge galvaneal steel. The floor structure is constructed of 12-gauge galvaneal and 1/8" deckplate steel. The step bumper is constructed of galvaneal and cold-rolled steel.

## Body Weight

11 ft RH and LH standard 2200 lb (998 kg)  
11 ft RH front raised 2250 lb (1020.6 kg)


## Body Substructure

Patented inverted A-frame design constructed of 12-gauge galvaneal material with integral crane box and rear outrigger housing.

## Electrical System

The electrical system consists of a central power distribution point in the crane box using automotive-style harnesses. The circuits use white wire with the circuit function printed every 3" (7.6 cm). The harness is protected by an overbraid that is heat- and cut-resistant.

## Substructure



## Doors

The doors are constructed of 14-gauge galvaneal steel with internal formed eaves and hemmed edges. The latches are a 3-point locking rotary T-handle style. They are constructed of cast steel with a powdercoat finish. The hinges are stainless steel with composite washers.


## Storage Capacity

11 ft RH and LH standard	120.5 cu ft (3.4 m <sup>3</sup> )
11 ft RH front raised	131.3 cu ft (3.7 m <sup>3</sup> )

## Options

- Drawers and drawer sets
- Standard adjustable shelves
- 3"H (7.6 cm) divided adjustable shelves
- Manual outriggers
- Workbench vises and vise plates
- Individual incandescent compartment lights
- Work lights
- Air systems
- Telescopic cranes up to 10,000 ft-lb (1.46 tm)

## Angle of Departure



17° (0.29 rad) with crank-down outrigger  
14° (0.24 rad) with crank-down outrigger

## Iowa Mold Tooling Co., Inc.

500 Highway 18 West • P.O. Box 189 • Garner, Iowa 50438-0189  
641-923-3711 • Fax: 641-923-6063 • www.imt.com

**800-247-5958**

IMT reserves the right to make changes in engineering, design, and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

IMT and the IMT logo are registered trademarks or trademarks of Iowa Mold Tooling Co., Inc., Garner, IA, USA.

© 2010 Iowa Mold Tooling Co., Inc. All Rights Reserved.