



VAN AIR[®]
A Lincoln Electric Company

CATEGORY 3



VAN AIR[®]
MOBILE POWER SOLUTIONS[®]

Welding Performance by

LINCOLN[®]
ELECTRIC

AIR N ARC 
330 DIESEL ALL-IN-ONE Power Systems[®]

40 CFM • 10 kW • 330 A

**Air N Arc[®] ALL-IN-ONE Power Systems[®]
and PowerFlex[™] Modular Systems**

Air N Arc[®] 150 • Air N Arc[®] 250-L • Air N Arc[®] 300 Series • PowerFlex[™] Series

Six Power Sources in One Unit — No Added Welders or Hydraulic Pumps Needed!

Air Compressor / Generator / Welder / Battery Boost / Battery Charge / Hydraulic Pump

The Air N Arc® ALL-IN-ONE Power Systems® provide up to six forms of power in one compact machine that increases performance while reducing cost and downtime. Featuring configurations consisting of a welder, generator, air compressor, battery booster, battery charger and hydraulic pump, the Air N Arc® product line provides you with a complete mobile workstation on the back of your truck.



AIR N ARC® 150



Reciprocating Air Compressor | Generator | Welder | Battery Booster | Battery Charger



SPECIFICATIONS

Engine	14 HP Kohler® or 20 HP Vanair® VNR680
Air Compressor	Type: Reciprocating CFM Rating: 20 CFM Max Pressure: 150 PSI
Generator	5kW Peak - 4.2kW Continuous, AC Power, 60 Hz, Single Phase, 120V and 240V Outlets
Welder	14 HP Stand-Alone: CC: 40-190A 20 HP with Remote Panel : CC: 40-150A, CV: 15-30V
Battery Charger/Booster	150A, 12/24V Boost, and 50A, 12V Charge (Standard for Vanair® VNR680 20 HP Engine Only)
Drive System	Belt Driven
Fuel Capacity	1.9 Gal. (Kohler® 14 HP) and 4.5 Gal., 11.5 Gal. or Tied to Chassis (Vanair® VNR680 20 HP)

Air N Arc® 150 Unit Dimensions (In.):
51.5L x 21.0W x 31.2H - 10 Gal. Kohler® 14 HP
50.7L x 19.2W x 40.8H - 30 Gal. Kohler® 14 HP
50.3L x 18.2W x 24.2H - Skid Mount Kohler® 14 HP

47.8L x 22.8W x 41.8H - 30 Gal. Vanair® VNR680 20 HP
47.8L x 21.3W x 25.3H - Skid Mount Vanair® VNR680 20 HP
Dry Weight (Lbs.): 290-487 (Depending on Platform)



AIR N ARC 250-L



Reciprocating Air Compressor | Generator | Welder | Battery Booster | Battery Charger



SPECIFICATIONS

Engine	23 HP Kohler®
Air Compressor	Type: Reciprocating CFM Rating: 24 CFM Max Pressure: 175 PSI
Generator	5kW Continuous, AC Power, 60 Hz, Single Phase, 120V and 240V Outlets
Welder	High Frequency DC Welding, 250A at 100% Duty Cycle CC: 40-250A, CV: 15-30V
Battery Charger/Booster	300A, 12/24V Boost, and 50A, 12V Charge
Drive System	Belt Driven
Fuel Capacity	11 Gal. or Tied to Chassis

Air N Arc® 250-L Unit Dimensions with Fittings (In.):
46.1L x 21.2W x 26.9H - Skid Mount
46.1L x 21.4W x 47.5H - 30 Gallon Air Tank
47.5L x 22.3W x 45.4H - 30 Gallon with Fuel Tank
Dry Weight (Lbs.): 370-550 (Depending on Platform)

Instrument Panel Dimensions with Fittings (In.):
Without Spacer: 13.13L x 6.8W x 13.25H
With Spacer: 13.13L x 11.0W x 13.25H



AIR N ARC 300 GAS & DIESEL



Rotary Screw Air Compressor | Generator | Welder | Battery Booster | Battery Charger



SPECIFICATIONS

Engine	Gas: 26.5 HP EFI Kohler®, Air Cooled Diesel: 25 HP Kubota®, Liquid Cooled (Tier 4 Compliant)
Air Compressor	Type: Rotary Screw CFM Rating: 40 CFM Max Pressure: 175 PSI
Generator	7kW Peak - 6.8kW Continuous, AC Power, 60 Hz, Single Phase, 120V and 240V Outlets
Welder	High Frequency DC Welding, 270A at 100% Duty Cycle CC: 40-300A, CV: 15-30V
Battery Charger/Booster	300A, 12/24V Boost, and 50A, 12V Charge
Drive System	Belt Driven
Fuel Capacity	12 Gal. Integral Tank (Optional Remote Tank or Tied to Chassis)

Air N Arc® 300 Gas Unit Dimensions (In.):
Foot Print: 47.1L x 21.5W x 30.9H
With Fittings: 47.1L x 24.6W x 30.9H
Dry Weight (Lbs.): 700



Air N Arc® 300 Diesel Unit Dimensions (In.):
Foot Print: 47.5L x 21.0W x 33.4H
With Fittings: 48.0L x 25.0W x 33.4H
Dry Weight (Lbs.): 870



AIR N ARC® 300 COMPACT GAS & DIESEL



Rotary Screw Air Compressor | Generator | Welder | Battery Booster | Battery Charger



*Low profile and ideal for slide out drawer application

SPECIFICATIONS

Engine	Gas: 26.5 HP Kohler®, Air Cooled Diesel: 25 HP Kubota®, Liquid Cooled (Tier 4 Compliant)
Air Compressor	Type: Rotary Screw CFM Rating: 40 CFM Max Pressure: 175 PSI
Generator	7kW Peak - 6.8kW Continuous, AC Power, 60 Hz, Single Phase, 120V and 240V Outlets
Welder	High Frequency DC Welding, 270A at 100% Duty Cycle CC: 40-300A, CV: 15-30V
Battery Charger/Booster	300A, 12/24V Boost, and 50A, 12V Charge
Drive System	Belt Driven
Fuel Capacity	Tied to Chassis

Air N Arc® 300 Compact Gas Unit Dimensions (In.):
Foot Print: 47.1L x 21.5W x 23.9H
With Fittings: 47.1L x 24.6W x 23.9H
Dry Weight (Lbs.): 650

Air N Arc® 300 Compact Diesel Unit Dimensions (In.):
Foot Print: 47.5L x 21.0W x 28.4H
With Fittings: 48.0L x 25.0W x 28.4H
Dry Weight (Lbs.): 775



Gas only

Included with Diesel Model

AIR N ARC® 300 HYDRAULIC

Now Featuring Auto On/Off Technology



Rotary Screw Air Compressor | Generator | Welder | Battery Booster | Battery Charger



SPECIFICATIONS

Drive System	Open Center Hydraulic
Hydraulic Requirements	19 GPM @ 2800 PSI Multifunction, 14.5 GPM @ 2500 PSI Single Function
Air Compressor	Type: Rotary Screw CFM Rating: 40 CFM Max Pressure: 175 PSI
Generator	7kW Peak - 6.8kW Continuous, AC Power, 60 Hz, Single Phase, 120V and 240V Outlets
Welder	High Frequency DC Welding, 270A at 100% Duty Cycle CC: 40-300A, CV: 15-30V
Battery Charger/Booster	300A, 12/24V Boost, and 50A, 12V Charge

Air N Arc® 300 Hydraulic Unit Dimensions (In.):
Foot Print: 48.7L x 21W x 30.9H
Dry Weight with Control Panel (Lbs.): 621

Ratings above are approximate and are based on 120°F hydraulic fluid temperature. Consult Vanair® for specific details.



AIR N ARC I-300



Rotary Screw Air Compressor | Generator | Welder | Battery Booster | Battery Charger | Hydraulics

SPECIFICATIONS

Engine	24.8 HP Kubota®, Liquid Cooled (Tier 4 Compliant)
Air Compressor	Type: Rotary Screw CFM Rating: 40 CFM Free Air at High Speed, 30 CFM Free Air at Idle Max Pressure: 175 PSI
Generator	7kW Peak - 6.8kW Continuous, AC Power, 60 Hz, Single Phase, 120V and 240V Outlets
Hydraulic Output	Up to 13 GPM, up to 3000 PSI (10.5 GPM Hydraulic Piston Pump)
Welder	High Frequency DC Welding, 270A at 100% Duty Cycle CC: 40-300A, CV: 15-30V
Battery Charger/Booster	300A, 12/24V Boost, and 50A, 12V Charge
Drive System	Belt Driven
Fuel Capacity	Tied to Chassis or Optional 12 Gal. Remote Tank

Air N Arc® I-300 Unit Dimensions (In.):
With Fittings: 47.1L x 25.2W x 33.4H
Foot Print: 47.1L x 21.0W x 33.4H
Dry Weight with Control Panel (Lbs.): 852

Ratings above are approximate and are based on 120°F hydraulic fluid temperature. Consult Vanair® for specific details.



AIR N ARC 330 DIESEL ALL-IN-ONE Power Systems

Featuring Lincoln Electric Welding Technology



Rotary Screw Air Compressor | Generator | Welder | Battery Booster | Battery Charger

SPECIFICATIONS

Engine	24.8HP Kubota® D902-E4B
Air Compressor	Type: Rotary Screw CFM Rating: 40 CFM Max Pressure: 175 PSI
Generator	Lincoln Electric 10kW Continuous, AC, Brushed, 60 Hz, Single Phase, 120V and 240V Outlets
Welder	Lincoln Electric DC Multi-Process Arc Welding, CC (Stick, Gouging, and TIG): 35-330A, CV (MIG and FCAW): 14-40V
Battery Charger/Booster	330A, 12/24V Boost, and 50A, 12/24V Charge
Drive System	Belt Driven Compressor, Direct Driven Generator and Welder
Fuel Capacity	11 Gal. with Bolt-On Frame Option

Air N Arc® 330 Diesel Unit Dimensions(In.):
Foot Print: 47.5L x 21.4W x 25.6H
With Fittings: 48.2L x 21.9W x 27.0H
Dry Weight (Lbs.): 750



Truck Engine Off, Power On - The Flexibility to Fit Your Needs

Hydraulics / Air Compressor / AC Generator Combinations

Vanair's PowerFlex™ modular power systems supply you with the power you need without the welders. The unique flexibility of the PowerFlex™ modular systems allows you to select just the functionality that best suits your work applications and budget. Whether it's hydraulics, air, electric or a combination of all three, Vanair's line of PowerFlex™ engine driven machines are the robust solution to provide the power you need to get the job done with the vehicle's engine turned off.

POWERFLEX™ AE



Rotary Screw Air Compressor | Generator

SPECIFICATIONS	
CFM Rating	40 CFM
Air Pressure	Up to 150 PSI
Compressor Type	Rotary Screw
AC Generator	6.8kW @ 60 Hz, 120/240V
Engine Type	25 HP Kubota® Tier 4 Final
Drive System	Belt Driven
Fuel Type	Diesel
Fuel Capacity	Integrated 12 Gal. Tanks or Tied to Chassis



* Available With and Without Integrated Fuel Tank



PowerFlex™ AE Unit Dimensions (In.):
47.6L X 21.0W X 33.4H**
Dry Weight (Lbs.): 790

POWERFLEX™ AE GAS



Rotary Screw Air Compressor | Generator

SPECIFICATIONS	
CFM Rating	40 CFM
Air Pressure	Up to 175 PSIG
Compressor Type	Rotary Screw
AC Generator	6.8kW @ 60 Hz, 120/240V
Engine Type	26.5 HP EFI Kohler®, Air Cooled
Drive System	Belt Driven
Fuel Type	Gas
Fuel Capacity	Integrated 12 Gal. Tank or Tied to Chassis



* Available With and Without Integrated Fuel Tank



PowerFlex™ AE Gas Unit Dimensions (In.):
With Fittings: 47.6L x 21.0W x 31.0H

5 Dry Weight (Lbs.): 675 with Fuel Tank, 630 Without Fuel Tank

POWERFLEX™

AEH



Rotary Screw Air Compressor | Generator | Hydraulics



SPECIFICATIONS	
CFM Rating	40 CFM
Air Pressure	Up to 150 PSI
Compressor Type	Rotary Screw
AC Generator	6.8kW @ 60 Hz, 120/240V
Hydraulic Flow*	Up to 13 GPM
Hydraulic Pressure*	Up to 3000 PSI
Engine Type	25 HP Kubota® Tier 4 Final
Drive System	Belt Driven
Fuel Type	Diesel
Fuel Capacity	12 Gallon or Tied to Chassis



PowerFlex™ AEH Unit Dimensions (In.):

47.6L X 21.0W X 33.4H**

Dry Weight (Lbs.): 870

*Ratings are approximate and are based on 120°F hydraulic fluid temperature. Hydraulic relief valve is set at 3300 PSI. Consult Vanair® for specific details.

**Dimensions listed are not a complete representation of total space necessary. Please consult Vanair® for overall space and air requirements.

POWERFLEX™

AH



Rotary Screw Air Compressor | Hydraulics



SPECIFICATIONS	
CFM Rating	40 CFM
Air Pressure	Up to 150 PSI
Compressor Type	Rotary Screw
Hydraulic Flow*	Up to 13 GPM
Hydraulic Pressure*	Up to 3000 PSI
Engine Type	25 HP Kubota® Tier 4 Final
Drive System	Belt Driven
Fuel Type	Diesel
Fuel Capacity	Tied to Chassis



PowerFlex™ AEH Unit Dimensions (In.):

47.6L X 21.0W X 33.4H**

Dry Weight (Lbs.): 802

*Ratings are approximate and are based on 120°F hydraulic fluid temperature. Hydraulic relief valve is set at 3300 PSI. Consult Vanair® for specific details.

**Dimensions listed are not a complete representation of total space necessary. Please consult Vanair® for overall space and air requirements.

The Original



Power Systems[®] Has Set The Standard



AIR COMPRESSOR



GENERATOR



WELDER



BATTERY BOOST



BATTERY CHARGE



HYDRAULIC PUMP



VANAIR[®]
A Lincoln Electric Company

800.526.8817 | vanair.com   